

# iEBMS URL Parameters

## AUD

### aud\_p1\_main (Audience Participation)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
AppCode	Application Code	SOP, AUD, REG, COE, etc.	The code of the application to which the page belongs. This is used to determine the path in the web server to locate files of the application. Also styles and sections of the page which can be set at the application level use this information.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
pagemode	Page Mode	AUD - Audience Mode, any other value provided for this URL will be perceived as Speaker Mode	Determines which mode the page assumes
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## BUM

### bum\_p1\_bulletins (Bulletin Management)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.

## BUM

### bum\_p1\_bulletins (Bulletin Management)

URLCode	URLName	PossibleValues	AdditionalNotes
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.

## COE

### coe\_p1\_all (Calendar of Events)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.

## COE

### coe\_p1\_all (Calendar of Events)

URLCode	URLName	PossibleValues	AdditionalNotes
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

### coe\_p1\_calendar (Calendar of Events)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## COM

### com\_p1\_all (Calendar of Meetings)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.

# COM

## com\_p1\_all (Calendar of Meetings)

URLCode	URLName	PossibleValues	AdditionalNotes
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## com\_p1\_calendar (Calendar of Meetings)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.

## COM

### com\_p1\_calendar (Calendar of Meetings)

URLCode	URLName	PossibleValues	AdditionalNotes
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## FOP

### fop\_p1\_select (Fulfillment Order Processing)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## GAT

### gat\_p1\_main (Fulfillment Order Processing)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.

## GAT

### gat\_p1\_main (Fulfillment Order Processing)

URLCode	URLName	PossibleValues	AdditionalNotes
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.
url	URL Number	1, 2, 3, 4, 5, 6, 7, 8, 9, 10	Specifies the URL that is chosen. URLs that are configured are matched with the URL Number and the user is redirected that URL if it is valid.

## INV

### inv\_p1\_list (Inventory Count Sheet)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
countsheettoedit	Count Sheet To Edi	Any valid inventory Batch ID CC321_BATCH_ID	This option is only valid in PDA mode of the configuration. Provides the batch ID using which the corresponding Count Sheet (inventory items and their details) can be accessed for display.

# INV

## inv\_p1\_list (Inventory Count Sheet)

URLCode	URLName	PossibleValues	AdditionalNotes
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
postback	Is Post Back?	Y,N	This option is only valid in PDA mode of the configuration. Indicates whether the page is doing a postback or not.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## inv\_p4\_gateway (Inventory Management)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.

## INV

### inv\_p4\_gateway (Inventory Management)

URLCode	URLName	PossibleValues	AdditionalNotes
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## JOB

### jobm\_p1\_main.aspx (Job Management - Enter Job)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

### jobm\_p5\_search (Job Management - Search Job)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.



## JOB

### jobm\_p5\_search (Job Management - Search Job)

URLCode	URLName	PossibleValues	AdditionalNotes
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## LOGON

### log\_p4\_add\_acct (Add Account Page)

URLCode	URLName	PossibleValues	AdditionalNotes
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

# MBD

## mbd\_p1\_all\_members (Member Directory - All Members)

URLCode	URLName	PossibleValues	AdditionalNotes
AT	Account Types	Any string codes of valid Account Types set on the configuration delimited by  (pipe)  Ex: ES 123	The members displayed on the page will be filtered by Account Types matching the values in the URL.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
MemChar	Member Character	"OTHERS", any combination of single characters denoting a alphabetical range or single alphabet.  Ex: OTHERS, A-C, T-Z, G	Filters the members displayed on the page based on the criteria given as the URL value. For Example, OTHERS: Members who's names start with value < A, A-N: Members with names starting with characters between A and N, Z: Members with names start with Z.
MP	Member Types	Any string codes of valid Member Types set on the configuration delimited by  (pipe)  Ex: ES 123	The members displayed on the page will be filtered by Member Types matching the values in the URL.
MS	Market Segments	Any string codes of valid Market Segments set on the configuration delimited by  (pipe)  Ex: A010 B162 B040	The members displayed on the page will be filtered by Market Segments matching the values in the URL.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.

# MBD

## mbd\_p1\_all\_members (Member Directory - All Members)

URLCode	URLName	PossibleValues	AdditionalNotes
PS	Products and Servi	Any string codes of valid Products and Services set on the configuration delimited by  (pipe)  Ex: A010 B162 B040	The members displayed on the page will be filtered by Products and Services matching the values in the URL.
RG	Regions	A string of codes of valid Regions set on the configuration delimited by  (pipe)  Ex: 10 80 13	The members displayed on the page will be filtered by Regions matching the values in the URL.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mbd\_p11\_contact\_chgs (Member Directory - Pending Contact Changes)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
acctsessionid	Account Session ID	Encrypted Session ID Value MM475_SESSION_ID	If a member changed or added a profile previously the Session Id of that session is passed in through this value. The Administrator can look at the changes that the member made to the profile that are stored in that session and then decide to approve them.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
cnt	Contact Code	*ADD , Any valid contact code	This value is used to redirect the Administrator to mbd_p8_all_chgs page if Admin Logon fails. The parameter value has contact code. If no contact code is provide the user is redirected to Pending Account Changes page. If the contact code is provided the changes done to that contact are displayed. If URL parameter has the aval *ADD the page opens in Add Contact Mode

## MBD

### mbd\_p11\_contact\_chgs (Member Directory - Pending Contact Changes)

URLCode	URLName	PossibleValues	AdditionalNotes
contactcode	Contact Code	*ADD, Any valid contact code	This parameter value is used to receive the contact code of the contact whose changes the administration wants to see. If *ADD is provided as the value the page loads in Add Contact Mode.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is a required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

### mbd\_p12\_member\_confirm (Member Directory - Member Details)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
AccountSearch	Account Code of M	Any valid Account Code EV870_ACCT_CODE	The URL value provides the account code used to search for a particular account
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	This works only when interfacing with OEP and requires OEP Session ID along with it. Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.

# MBD

## mbd\_p12\_member\_confirm (Member Directory - Member Details)

URLCode	URLName	PossibleValues	AdditionalNotes
member	Member Account C	Any valid Account Code of a member. EV870_ACCT_CODE	Loads the page with details of the member whose account code is provided through the URL value.
oc	Organization Code	<XX> Organization code represented by two characters	This works only when interfacing with OEP and requires and OEP Session ID along with it. Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mbd\_p2\_one\_member (Member Directory - Member Details)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
keyword	Search Key Word	A single Keyword	The value provided replaces wild card Key "@KEYWORD" that it is present in any of the borders. This in turn adds to the search criteria for the search links on the side bars.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
searchtype	Search Type	A single keyword	The value provided replaces wild card Key "@SEARCH" that it is present in any of the borders. This in turn determines the search criteria for the search links on the side bars.

# MBD

## mbd\_p2\_one\_member (Member Directory - Member Details)

URLCode	URLName	PossibleValues	AdditionalNotes
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mbd\_p22\_report (Membership Report)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
member	Member Account C	Any valid Account Code of a member. EV870_ACCT_CODE	Loads the page with details of the member whose account code is provided through the URL value.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
reportname	Report Name	Encrypted Report Name	The name of the report being generated. It is used to find the appropriate crystal report. This value is encoded and encrypted. This is a required value.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mbd\_p23\_add\_member (Member Directory - Become a Member - Add Member Details)

URLCode	URLName	PossibleValues	AdditionalNotes
---------	---------	----------------	-----------------

# MBD

## mbd\_p23\_add\_member (Member Directory - Become a Member - Add Member Details)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mbd\_p25\_assign\_admin (MBD - Assign Adminstrative Member Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.

# MBD

## mbd\_p25\_assign\_admin (MBD - Assign Administrative Member Page)

URLCode	URLName	PossibleValues	AdditionalNotes
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mbd\_p26\_all\_member\_print (Member Directory - All Members)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
AT	Account Types	Any string codes of valid Account Types set on the configuration delimited by  (pipe)  Ex: ES 123	The members displayed on the page will be filtered by Account Types matching the values in the URL.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
MemChar	Member Character	"OTHERS", any combination of single characters denoting a alphabetical range or single alphabet.  Ex: OTHERS, A-C, T-Z, G	Filters the members displayed on the page based on the criteria given as the URL value. For Example, OTHERS: Members who's names start with value < A, A-N: Members with names starting with characters between A and N, Z: Members with names start with Z.



# MBD

## mbd\_p26\_all\_member\_print (Member Directory - All Members)

URLCode	URLName	PossibleValues	AdditionalNotes
MP	Member Types	Any string codes of valid Member Types set on the configuration delimited by  (pipe)  Ex: ES 123	The members displayed on the page will be filtered by Member Types matching the values in the URL.
MS	Market Segments	Any string codes of valid Market Segments set on the configuration delimited by  (pipe)  Ex: A010 B162 B040	The members displayed on the page will be filtered by Market Segments matching the values in the URL.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
PS	Products and Servi	Any string codes of valid Products and Services set on the configuration delimited by  (pipe)  Ex: A010 B162 B040	The members displayed on the page will be filtered by Products and Services matching the values in the URL.
RG	Regions	A string of codes of valid Regions set on the configuration delimited by  (pipe)  Ex: 10 80 13	The members displayed on the page will be filtered by Regions matching the values in the URL.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mbd\_p3\_searchpage (Member Directory - search)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.

# MBD

## mbd\_p3\_searchpage (Member Directory - search)

URLCode	URLName	PossibleValues	AdditionalNotes
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mbd\_p4\_productlist (Member Directory - Products And Services List)

URLCode	URLName	PossibleValues	AdditionalNotes
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mbd\_p5\_profile\_editor\_list (Member Directory - Profile Editor List)

URLCode	URLName	PossibleValues	AdditionalNotes
---------	---------	----------------	-----------------

# MBD

## mbd\_p5\_profile\_editor\_list (Member Directory - Profile Editor List)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mbd\_p6\_profile\_editor\_list (Member Directory - Profile Editor - Edit Member Details)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.

# MBD

## mbd\_p6\_profile\_editor\_list (Member Directory - Profile Editor - Edit Member Details)

URLCode	URLName	PossibleValues	AdditionalNotes
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mbd\_p8\_all\_chgs (Member Directory - Profile Editor List)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
acctsessionid	Account Session ID	Encrypted Session ID Value MM475_SESSION_ID	Id a member changed or added a profile previously the Session Id of that session is passed in through this value. The Administrator can look at the changes that the member made to the profile that are stored in that session and then decide to approve them.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
cnt	Contact Code	*ADD , Any valid contact code	The parameter value has contact code. If no contact code is provide the user is redirected to Pending Account Changes page. If the contact code is provided the changes done to that contact are displayed. If URL parameter has the aval *ADD the page opens in Add Contact Mode
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.

# MBD

## mbd\_p8\_all\_chgs (Member Directory - Profile Editor List)

URLCode	URLName	PossibleValues	AdditionalNotes
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mbd\_p9\_chgs (Member Directory - Pending Account Changes)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
acctsessionid	Account Session ID	Encrypted Session ID Value MM475_SESSION_ID	If a member changed or added a profile previously the Session Id of that session is passed in through this value. The Administrator can look at the changes that the member made to the profile that are stored in that session and then decide to approve them.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
cnt	Contact Code	*ADD , Any valid contact code	The parameter value has contact code. If no contact code is provide the user is redirected to Pending Account Changes page. If the contact code is provided the changes done to that contact are displayed. If URL parameter has the aval *ADD the page opens in Add Contact Mode
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.

## MBD

### mbd\_p9\_chgs (Member Directory - Pending Account Changes)

URLCode	URLName	PossibleValues	AdditionalNotes
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## MPS

### mps\_p1\_main (Membership Point-Of-Sale Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

### mps\_p12\_enter\_name (Add Member)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.

# MPS

## mps\_p12\_enter\_name (Add Member)

URLCode	URLName	PossibleValues	AdditionalNotes
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mps\_p13\_enter\_Address (Add Member)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.

# MPS

## mps\_p13\_enter\_Address (Add Member)

URLCode	URLName	PossibleValues	AdditionalNotes
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mps\_p14\_enter\_comm (Add Member)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mps\_p2\_validate\_main (Validate Membership Search Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.



# MPS

## mps\_p2\_validate\_main (Validate Membership Search Page)

URLCode	URLName	PossibleValues	AdditionalNotes
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mps\_p3\_validate\_searchby (Validate Membership Search Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
searchagain	Search Again	Y, N	When the parameter vauue is Y the page repopulates Account Code, First Name, Last Name and Company Name from the session XML

# MPS

## mps\_p3\_validate\_searchby (Validate Membership Search Page)

URLCode	URLName	PossibleValues	AdditionalNotes
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mps\_p4\_validate\_by\_scan (Validate Membership Search Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
searchagain	Search Again	Y, N	When the parameter vauue is Y the page repopulates Account Code, First Name, Last Name and Company Name from the session XML
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mps\_p8\_select\_type\_aspx (Add Member)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.

# MPS

## mps\_p8\_select\_type.aspx (Add Member)

URLCode	URLName	PossibleValues	AdditionalNotes
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
postback	Post Back	Y,N	when the parameter value is Y it indicates that the the page is being returned to from other pages.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## mps\_p9\_add\_items (Add Member)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.

## MPS

### mps\_p9\_add\_items (Add Member)

URLCode	URLName	PossibleValues	AdditionalNotes
postback	Post Back	Y,N	when the parameter value is Y it indicates that the the page is being returned to from other pages.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## MTR

### mtr\_p1\_add (Add Meeting Request Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

### mtr\_p4\_list (Meeting List)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.

## MTR

### mtr\_p4\_list (Meeting List)

URLCode	URLName	PossibleValues	AdditionalNotes
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## OEP

### oep\_p1\_exhibitors (Online Exhibitor Planner)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
BR	Break Line	Y,N	A configuration value that determines if line breaks are used in the HTML markup of the page.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.

# OEP

## oep\_p1\_exhibitors (Online Exhibitor Planner)

URLCode	URLName	PossibleValues	AdditionalNotes
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
edit	Lookup Mode: Edit	Y, N	Determines if the exhibitor profiles that are displayed are the ones that can be edited by the user who is logged in at the moment.
eventid	Event ID	Any valid Event ID in EBMS EV200_EVT_ID	Provides the application with the event information. Used to retrieve related information such as pricelists, orders, etc.
keyword	Search Key Word	A single Keyword	The value provided replaces wild card Key "@KEYWORD" that it is present in any of the borders. This in turn adds to the search criteria for the search links on the side bars.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
mylist	Lookup Mode: My	Y, N	Determines if the exhibitor list that is displayed is list of the exhibitors that the user who is logged in is following.
searchtype	Search Type	A single keyword	The value provided replaces wild card Key "@SEARCH" that it is present in any of the borders. This in turn determines the search criteria for the search links on the side bars.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## oep\_p13\_exhibitors (Online Exhibitor Planner)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
BR	Break Line	Y,N	A configuration value that determines if line breaks are used in the HTML markup of the page.

# OEP

## oep\_p13\_exhibitors (Online Exhibitor Planner)

URLCode	URLName	PossibleValues	AdditionalNotes
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
ct	Configuration Type	Any valid code of the the Configuration Code created for this application.	The URL parameter value provides the type of the configuration to be used. This value is usually used in conjunction with other values like OrgCode and eventid to determine the unique configuration of the application to be used.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
edit	Lookup Mode: Edit	Y, N	Determines if the exhibitor profiles that are displayed are the ones that can be edited by the user who is logged in at the moment.
eventid	Event ID	Any valid Event ID in EBMS EV200_EVT_ID	Provides the application with the event information. Used to retrieve related information such as pricelists, orders, etc.
keyword	Search Key Word	A single Keyword	The value provided replaces wild card Key "@KEYWORD" that it is present in any of the borders. This in turn adds to the search criteria for the search links on the side bars.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
mylist	Lookup Mode: My	Y, N	The exhibitor list that is displayed is list of the exhibitors that the user who is logged in is following.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
ordernbr	Order Number	The Order Number of any valid order.	The Order Number of the order that the exhibitor has placed, that also contians the resources that identify an exhibitor.
searchtype	Search Type	A single keyword	The value provided replaces wild card Key "@SEARCH" that it is present in any of the borders. This in turn determines the search criteria for the search links on the side bars.

## OEP

### oep\_p13\_exhibitors (Online Exhibitor Planner)

URLCode	URLName	PossibleValues	AdditionalNotes
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

### oep\_p14\_virtualbooth (Virtual Booth)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
keyword	Search Key Word	A single Keyword	The value provided replaces wild card Key "@KEYWORD" that it is present in any of the borders. This in turn adds to the search criteria for the search links on the side bars.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
ordernbr	Order Number	The Order Number of any valid order.	The Order Number of the order that the exhibitor has placed, that also contains the resources that identify an exhibitor. This is a Required URL.
searchtype	Search Type	A single keyword	The value provided replaces wild card Key "@SEARCH" that it is present in any of the borders. This in turn determines the search criteria for the search links on the side bars.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

### oep\_p5\_floorplan (Event Floor Plan Details)

URLCode	URLName	PossibleValues	AdditionalNotes
---------	---------	----------------	-----------------



## OEP

### oep\_p5\_floorplan (Event Floor Plan Details)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
boothnbr	Booth Number	Any valid Booth Number of a Booth placed on the Floor plan of the particular event.	The value determines which booth is highlighted on the floor plan.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
ct	Configuration Type	Any valid code of the the Configuration Code created for this application.	The URL parameter value provides the type of the configuration to be used. This value is usually used in conjunction with other values like OrgCode and eventid to determine the unique configuration of the application to be used.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
eventid	Event ID	Any valid Event ID in EBMS EV200_EVT_ID	Provides the application with the event information. Used to retrieve related information such as pricelists, orders, etc.
keyword	Search Key Word	A single Keyword	The value provided replaces wild card Key "@KEYWORD" that it is present in any of the borders. This in turn adds to the search criteria for the search links on the side bars.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
NoBorders	No Borders	Y,N	The value determines if the page borders are displayed on the page on the page or not.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
ordernbr	Order Number	The Order Number of any valid order.	The Order Number of the order that the exhibitor has placed, that also contians the resources that identify an account as an exhibitor.

## OEP

### oep\_p5\_floorplan (Event Floor Plan Details)

URLCode	URLName	PossibleValues	AdditionalNotes
Reg	Registrant Account	Any valid account code of a registrant	
searchagain	Search Again	Y, N	When the parameter value is Y the page repopulates Account Code, First Name, Last Name and Company Name from the session XML
searchtype	Search Type	A single keyword	The value provided replaces wild card Key "@SEARCH" that it is present in any of the borders. This in turn determines the search criteria for the search links on the side bars.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## PAY

### pay\_p1\_list (Payment Portal - List Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is a required URL parameter.
ordernbr	Order Number	The Order Number of any valid order.	The Order Number of the order for which the payment is made.

## PAY

### pay\_p1\_list (Payment Portal - List Page)

URLCode	URLName	PossibleValues	AdditionalNotes
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

### pay\_p2\_history (Payment Portal - Payment History Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## PTL

### ptl\_p1\_main (Event/Assignment Information)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.

# PTL

## ptl\_p1\_main (Event/Assignment Information)

URLCode	URLName	PossibleValues	AdditionalNotes
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## ptl\_p6\_manage (Portal Access Information)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.

## PTL

### ptl\_p6\_manage (Portal Access Information)

URLCode	URLName	PossibleValues	AdditionalNotes
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## REG

### reg\_p1\_form (Registration Selection Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
coecc	Calendar Of Events	Any valid Calendar Of Events application configuration code.	Contains the configuration code of the Calendar of Events configuration that is linked with the current application configuration.
contactcode	Contact Code	*ADD, Any valid contact code	This parameter value is used to receive the contact code of the contact whose changes the administration wants to see. If *ADD is provided as the value the page loads in Add Contact Mode.
ct	Configuration Type	Any valid code of the Configuration Code created for this application.	The URL parameter value provides the type of the configuration to be used. This value is usually used in conjunction with other values like OrgCode and eventid to determine the unique configuration of the application to be used.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
Event	Registration Event ID	Any valid Registration Event ID	The Event ID for which the registrant indicated by Reg parameter. Please look at Reg parameter for more information.

## REG

### reg\_p1\_form (Registration Selection Page)

URLCode	URLName	PossibleValues	AdditionalNotes
eventid	Event ID	Any valid Event ID in EBMS EV200_EVT_ID	Provides the application with the event information. Used to retrieve related information such as pricelists, orders, etc.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
Reg	Registrant Account	Any valid account code of a registrant	This value along with the Event parameter will direct the user to Edit Registrant page automatically
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

### reg\_p10\_split\_order (Registration Order Search Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
ct	Configuration Type	Any valid code of the the Configuration Code created for this application.	The URL parameter value provides the type of the configuration to be used. This value is usually used in conjunction with other values like OrgCode and eventid to determine the unique configuration of the application to be used.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
eventid	Event ID	Any valid Event ID in EBMS EV200_EVT_ID	Provides the application with the event information. Used to retrieve related information such as pricelists, orders, etc.

## REG

### reg\_p10\_split\_order (Registration Order Search Page)

URLCode	URLName	PossibleValues	AdditionalNotes
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
RPLOrderMode	Registration Portal: Y,N		Indicated if the current page is accessed from RPL.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

### reg\_p9\_orders (Registration Orders Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
SearchEventID	Search Event ID	Any valid Event ID EV200_EVT_ID	The orders displayed on the page are fitlered for the Event provided by this value
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## REG

### reg\_p9\_orders (Registration Orders Page)

URLCode	URLName	PossibleValues	AdditionalNotes
sortby (reg)	Sort By Columns	01 - Order Number 02 - Order Date 03 - Event Description 04 - Order Total	<p>The orders displayed on the page are sorted by the order of columns provided by this value.</p> <p>By default, the page will be sorted in ascending order. To sort in descending order append the character 'd' or 'D' to the sortby string. e.g. sortby=01d. The system will also accept the character 'a' or 'A' for ascending.</p> <p>It is possible to sort on multiple columns. This can be done by separating each column to be sorted by a comma. e.g. sortby=01d,02a,03a</p>

## RPL

### rpl\_p1\_main (Registration Portal)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
eventid	Event ID	Any valid Event ID in EBMS EV200_EVT_ID	Provides the application with the event information. Used to retrieve related information such as pricelists, orders, etc.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.



# SOP

## sop\_p1\_steps\_booth (STEP 1 - Service Order Processing)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
eventid	Event ID	Any valid Event ID in EBMS EV200_EVT_ID	Provides the application with the event information. Used to retrieve related information such as pricelists, orders, etc.
fullscreen	Show Full Screen	Y,N	If the configuration is setup to allow Full Screen, this parameter value will determine if the application is going to be displayed as a full screen or not.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
longnote	Long Note Class Ov	Any valid note class	Overrides the class used for displaying long notes.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is a required URL parameter.
orderform	Order Form Selecte	The code of any valid order form configured for display on the configuration.	The value determines which order form is selected by default.
po	Purchase Order Nu	Valid Purchase Order Number	The value provides the application with the Purchase Order Number that should be used for payment. When the order is placed this Purchase Order Number is stored on the order(ER100_PO_NBR) that is created.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.
shortnote	Short Note Class O	Any valid note class	Overrides the class used for displaying short notes.

## SOP

### sop\_p10\_orders (Service Order Processing Orders Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
eventid	Event ID	Any valid Event ID in EBMS EV200_EVT_ID	If an Event ID is provided the orders displayed on the page are filtered for the event and only the orders for that event are shown.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
ordernbr	Order Number	The Order Number of any valid order.	If this value is provided the user is taken directly to the edit order page for that order instead of displaying a list of orders.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.
sortBy (sop)	Sort By Columns	01 - Order Number 02 - Order Date 03 - Work Order Due Date 04 - Order Status 05 - Event Description 06 - Price List Order Total 07 - Order Account 08 - Order Contact 09 - Booth Number 10 - Order Entered Date 11 - Order Updated Date	The orders displayed on the page are sorted by the order of columns provided by this value.  By default, the page will be sorted in ascending order. To sort in descending order append the character 'd' or 'D' to the sortBy string. E.g. sortBy=01d. The system will also accept the character 'a' or 'A' for ascending.  It is possible to sort on multiple columns. This can be done by separating each column to be sorted by a comma. E.g. sortBy=01d,02a,03a

## SPA

# SPA

## spa\_p1\_authors (Abstract Authors Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## spa\_p5\_evallist (Evaluator's Abstract List)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.

## SPA

### spa\_p5\_evallist (Evaluator's Abstract List)

URLCode	URLName	PossibleValues	AdditionalNotes
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

### spa\_p6\_mgrlist (Manager's Abstract List)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

### spa\_p8\_agenda (Session Agenda)

URLCode	URLName	PossibleValues	AdditionalNotes
---------	---------	----------------	-----------------

## SPA

### spa\_p8\_agenda (Session Agenda)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## VA

### va\_p1\_search (Venue Availability Search)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.

**va\_p1\_search (Venue Availability Search)**

<b>URLCode</b>	<b>URLName</b>	<b>PossibleValues</b>	<b>AdditionalNotes</b>
FromDate	Availability Search	Valid Date in Local Date format  Eg: 08/13/2011, 08-13-2011	If the mode is onedate, the FromDate is defaulted in as the search date. If the mode is multirate the FromDate is defaulted in as the default start date.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
mode	Mode	Page Dependent	Determines if the availability search is for a single date or for a date range. This in turn determines if the booking is being done over multiple days or a single day.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
po	Purchase Order Nu	Valid Purchase Order Number	The value provides the application with the Purchase Order Number that should be used for payment. When the booking order is placed this Purchase Order Number is defaulted into the payment information.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.
ToDate	Availability Search	Valid Date in Local Date format  Eg: 08/13/2011, 08-13-2011	This parameter is only valid for multirate mode. The Search End Date is defaulted from this value.

**va\_p5\_booking\_calendar (Booking Calendar)**

<b>URLCode</b>	<b>URLName</b>	<b>PossibleValues</b>	<b>AdditionalNotes</b>
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.

## VA

### va\_p5\_booking\_calendar (Booking Calendar)

URLCode	URLName	PossibleValues	AdditionalNotes
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.
startdate	Default Start Date	Valid Date in Local Date format  Eg: 08/13/2011, 08-13-2011	This parameters defaults in the start date from which the spans are displayed on the Booking Calendar.

## VBK

### vbk\_p1\_main (Venue Booking Kiosk Add/Edit Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.

## VBK

### vbk\_p1\_main (Venue Booking Kiosk Add/Edit Page)

URLCode	URLName	PossibleValues	AdditionalNotes
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
login	Force Login	Y,N	This value when set to Y forces the user to Login before using the application.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.
startdate	Default Start Date	Valid Date in Local Date format  Eg: 08/13/2011, 08-13-2011	This parameters defaults in the start date from which the spans are displayed on the Booking Calendar.
startdate	Default Start Date	Valid Date in Local Date format  Eg: 08/13/2011, 08-13-2011	This parameters defaults in the start date for the space search.

## WBE

### wbe\_p1\_main (Event Website Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.



# WBE

## wbe\_p1\_main (Event Website Page)

URLCode	URLName	PossibleValues	AdditionalNotes
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## wbe\_p3\_registrants (Event Website Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
eventid	Event ID	Any valid Event ID in EBMS EV200_EVT_ID	Provides the application with the event information. Used to retrieve related information such as pricelists, orders and registrants
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.

## WBE

### wbe\_p3\_registrants (Event Website Page)

URLCode	URLName	PossibleValues	AdditionalNotes
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.

## WOM

### wom\_p1\_list (Assigned Work Orders Page, Manage Work Orders Page)

URLCode	URLName	PossibleValues	AdditionalNotes
accountcode	Account Code	Any valid Account Code that is Internet Logon enabled. EV870_ACCT_CODE	This parameter comes into play if the application requires login. If the corresponding LOGON configuration has the Allow Auto Logon With Account Code On URL option turned on then this parameter with a valid value will login the user automatically.
cc	Configuration Code	Configuration Code of any of the configurations of the application present in EBMS for that particular organization.	Provides Configuration Code of the particular configuration of the application to be used. This is a required parameter.
dict	Dictionary Number	Any valid existing EBMS dictionary number	Used to determine the dictionary number that will be used to retrieve the phrases displayed on the page. Dictionaries can be different not only in phrases but also in languages.
lang	Language Code	Any valid language code for the languages setup in EBMS	Used to determine the language preference for the phrases displayed on the page.
oc	Organization Code	<XX> Organization code represented by two characters	Provides Organization Code. This is are required URL parameter.
sessionid	Session ID	Encrypted Session ID Value MM475_SESSION_ID	Holds the value of the current session. This is unique per session. Is always encrypted on the URL.